

In the Claims:

Please amend claims 5, 7, 9, 10, 15-17 and 18 as follows:

1. (Original) A liquid crystal display device comprising a liquid crystal layer and a pair of electrodes for applying voltage onto the liquid crystal installed on both sides of said liquid crystal layer, the liquid crystal layer and pair of electrodes being sandwiched by a pair of substrates, wherein:

said liquid crystal layer has a section obtained by polymerizing a polymerizable compound in the presence of said liquid crystal through selective irradiation of active energy rays over the substrate surface.

2. (Original) A liquid crystal display device comprising a liquid crystal layer and a pair of electrodes for applying voltage onto the liquid crystal installed on both sides of said liquid crystal layer, the liquid crystal layer and pair of electrodes being sandwiched by a pair of substrates, wherein:

said liquid crystal layer has a section obtained by polymerizing a polymerizable compound in the presence of said liquid crystal through selective irradiation of active energy rays over the substrate surface without voltage application.

3. (Original) A liquid crystal display device according to claim 1 or 2, wherein said liquid crystal layer has a section obtained by polymerization through selective irradiation of active energy rays followed by irradiation of active energy rays all over the substrate surface with voltage application.

4. (Original) A liquid crystal display device according to claim 3, wherein at least one of said two irradiations of active energy rays has been carried out along a direction tilted from the normal to the substrate surface.

5. (Currently Amended) A liquid crystal display device according to one of ~~claims 1 to 4~~claim 1 or 2, where said liquid crystal layer shows a specific light shielding pattern caused by the alignment of liquid crystal molecules when a voltage is applied after said irradiation or irradiations of active energy rays.

6. (Original) A liquid crystal display device according to claim 5, wherein said specific light shielding pattern caused by the alignment of liquid crystal molecules comprises at least one pattern selected from the group consisting of a lattice pattern, a crisscross pattern, a pattern in the shape of stripes and a pattern in the shape of stripes with bends.

7. (Currently Amended) A liquid crystal display device according to one of ~~claims 1 to 6~~claim 1 or 2, wherein a section or sections (alignment direction controlling section or sections) that show an effect to control the alignment directions caused by a polymerized liquid crystal composition obtained by the selective irradiation of active energy rays are installed on either one or both of the surfaces which contact the liquid crystal layer (liquid crystal layer contacting surfaces).

8. (Original) A liquid crystal display device according to claim 7, wherein at least one means selected from the group consisting of protrusions, depressions and a slit pattern in an electrode is installed on the surface or surfaces which contact the liquid crystal layer (liquid crystal layer contacting surface or surfaces).

9. (Currently Amended) A liquid crystal display device according to one of ~~claims 1 to 8~~ claim 1 or 2, wherein said liquid crystal has a negative dielectric constant anisotropy, and is aligned in the direction vertical to the substrate surface when no voltage is applied after said irradiation or irradiations of active energy rays.

10. (Currently Amended) A liquid crystal display device according to one of ~~claims 1 to 9~~ claim 1 or 2, wherein:

a first polarizer and a second polarizer are installed each on one of the outer sides of said pair of substrates so that the absorption axes of the two polarizers are perpendicular to each other;

a first 1/4 wavelength plate is installed between one of said substrates and the first polarizer;

a second 1/4 wavelength plate is installed between the other one of said substrates and the second polarizer; and,

the absorption axis of the first polarizer is at 45° from the phase delay axis of the first 1/4 wavelength plate, the absorption axis of the second polarizer is at 45° from the phase delay axis of the second 1/4 wavelength plate, and the phase delay axis of the first 1/4 wavelength plate and the phase delay axis of the second 1/4

wavelength plate are perpendicular to each other.

11. (Original) A method for manufacturing a liquid crystal display device comprising a liquid crystal layer and a pair of electrodes for applying voltage onto the liquid crystal installed on both sides of said liquid crystal layer, the liquid crystal layer and pair of electrodes being installed between a pair of substrates, said method comprising:

forming said liquid crystal layer from a liquid crystal composition comprising a liquid crystal and a polymerizable compound;

polymerizing part of said polymerizable compound by selective irradiation of active energy rays over the substrate surface with no voltage application; and then,

polymerizing said polymerizable compound by irradiation of active energy rays all over the substrate surface with voltage application.

12. (Original) A method for manufacturing a liquid crystal display device according to claim 11, wherein a photomask is used for said selective irradiation of active energy rays.

13. (Original) A method for manufacturing a liquid crystal display device according to claim 12, wherein the light shielding section width and opening width of said photomask are each in the range of 2 to 100 mm.

14. (Original) A method for manufacturing a liquid crystal display device according to one of claims 11 to 13, wherein said active energy rays are ultraviolet rays.

15. (Currently Amended) A method for manufacturing a liquid crystal display device according to one of claims 11 ~~to 14~~ to 13, wherein said irradiations of active energy rays are carried out so that said liquid crystal layer shows a specific light shielding pattern caused by the alignment of liquid crystal molecules when a voltage is applied after the irradiations of active energy rays.

16. (Currently Amended) A method for manufacturing a liquid crystal display device according to one of claims 11 ~~to 15~~ to 13, wherein at least one of said two irradiations of active energy rays is carried out along a direction tilted from the normal to the substrate surface.

17. (Currently Amended) A method for manufacturing a liquid crystal display device according to one of claims 11 ~~to 16~~ to 13, wherein said irradiation of active energy rays at no voltage application is carried out so that a section or sections (alignment direction controlling section or sections) that show an effect to control the alignment directions caused by a polymerized liquid crystal composition obtained by the selective irradiation of active energy rays are generated on either one or both of the surfaces which contact the liquid crystal layer (liquid crystal layer contacting surfaces).

18. (Currently Amended) A method for manufacturing a liquid crystal display device according to one of claims ~~11 to 17~~to 13, wherein at least one means selected from the group consisting of protrusions, depressions and a slit pattern installed in an electrode is installed on the surface or surfaces which contact the liquid crystal layer (liquid crystal layer contacting surface or surfaces).